

PLUMBER, HVACR, FIELD SERVICES PACKAGES



OPTION 1 - FT/L, FT/MH Includes: 3-ft. fold-down crane, pedestal, reinforcement kit

LOW | MEDIUM | HIGH ROOF 130WB | 148WB



3 FT. FOLD-DOWN CRANE Max Load - 650 lbs. 12 V DC

MUNICIPALITY, CONTRACTORS, FIELD SERVICES PACKAGES



OPTION 2 - SB/R Includes: 4 ft. crane, pedestal, reinforcement kit

CORNER MOUNT RIGHT SIDE



4 FT. CRANE Max Load - 900 lbs. 12 V DC

PLUMBER, HVACR, FIELD SERVICES PACKAGES



OPTION 3 - ESB - P30 Includes: 3-ft. fold-down crane, pedestal, reinforcement kit

LOW | MEDIUM | HIGH ROOF



3 FT. FOLD-DOWN CRANE Max Load - 650 lbs.

12 V DC

MUNICIPALITY, CONTRACTORS, FIELD SERVICES PACKAGES



OPTION 1 - PL Includes: 4 ft. crane, pedestal,

reinforcement kit

OPTION 1M-PL Includes: 4 ft. manual crane, pedestal, reinforcement kit



4 FT. CRANE Max Load - 900 lbs. 12 V DC

CONTRACTORS, FIELD SERVICES, WEEKEND WARRIORS PACKAGES



OPTION 3 - PU Includes: 4 ft. crane, pedestal, reinforcement kit

F250 | F350 (2017 forward)



4 FT. CRANE Max Load - 900 lbs. 12 V DC

CONTRACTORS, FIELD SERVICES, WEEKEND WARRIORS PACKAGES



OPTION 4M-PU Includes: 4 ft. manual crane, receiver hitch mount

No installation required



4 FT. CRANE Max Load - 700 lbs. Manual

FLEET LIFTING SOLUTIONS














VANS

SERVICE BODIES

ENCLOSED BODIES

PLATFORMS

PICKUPS











SPITZLIFT:

- Meets ASME, OSHA, and CE standards.
- Made of lightweight aircraft grade aluminum.
- Every crane is tested and comes with a load test certificate.
- Custom solutions are available to meet specialty applications.
- Components are manufactured according to ISO compliance.
- Vehicle specific pedestals and reinforcement kits provided.

3 YEAR STANDARD WARRANTY

(Will match OEM warranty up to 6 years)

SERVICE VEHICLE CRANE OPTIONS:

- Boom Length: 3 ft. or 4 ft.
- Manual crane with load control built-in brake
- Electric Crane: DC or AC (lifting speed 22 ft. per/min.)

ADDITIONAL OPTIONS:

- Strap: 2" UV resistant webbing. Abrasion resistant edge
- Wire rope: 3/16" aircraft-grade cable. 3600 lbs. rating
- Synthetic rope: 3/16" 4900 lbs. rating. Non-rotational, fatigue, abrasion, UV & wear resistant

SAFETY FEATURES OF ELECTRIC CRANES:

- Safety release auxiliary handle
- Circuit breaker system for overload protection
- Dynamic and disc brake dual load control system

WWW.SPITZLIFT.COM | 619.713.5061

LIGHTWEIGHT

INSTALLED WEIGHT IS LESS THAN 100 LBS.

SAFE & EFFICIENT

MITIGATES INJURIES AND INCREASES PRODUCTIVITY

PAYLOAD FRIENDLY

TOTAL IMPACT TO VEHICLE IS LESS THAN 100 LBS.

BUILT TO LIFT

